

Motor				Motor				System colours		
AM75 230 V AC	-	1200	12,5	56,0	AM50 230 V AC	-	1200	12,5	50,0	

Standard includes curtain track Torro in colour white with ceiling brackets and runners (10 runners / 1 m track).

System is delivered without programmed end positions (please follow instructions in the manual attached to the product).

Motor AM75 RF - potential-free or/and radio control (RF)

Motor AM75 SW RF - phase control AC, potential-free or/and radio control (RF)

Motor AM50 EB RF radio control (RF) - only in white colour

Maximum width of the system without rail connector - 7 m.

Manual control - curtain allows manually control the curtain after power failure.

Tandem - two motors installed on opposite sides of the rail.

Possibility of RS485 or potential-free control.

Slight differences between colours of system components are permitted.

The possibility of connecting curtain track system to specific intelligent control system should be consulted before ordering.

Rail

Glider

Brackets

ceiling

wall extension adjustable

Ripple fold

Touch Motion

UP

By using special gliders and tape, we achieve a ripple effect.

Start the motor by simply pulling the fabric. It is not possible to stop the curtain track with this function.

Solution for suspended ceiling enabling installation of the motor and cabling over the ceiling.

Maximum system load

	Rail type	load (weight of the fabric)* [kg]					
		up to 4 m		up to 8 m		up to 12 m	
AM50 EB RF AM75 RF AM75 SW RF	straight rail	50	50	56	87	50	87
	1 curve	50	50	43	62	37	62
	2 curves	37	37	31	37	25	37
	large curve	26	26	20	23		23

* max. load of a glider 1.25 kg
with Microflex option the curtain track loading limit is 80% of the value listed in the table above

Tandem

Special extended gliders allow to use the Microflex fabric holders, which make it possible to regulate fabric height. Option not available when using a rail connector.

tandem AM75 **

tandem AM50 EB RF

glider

ceiling bracket

wall extension

rail connector

microflex 95 mm (pc.)

microflex 95 mm (pc.)

microflex 95 mm (pc.)

bending with radius 30 cm / 45 cm

bending large curve

ripple fold tape (white, black, transparent) (m) - Snap

ripple fold tape (m) - Wave

RJ12 control cable

